



 Onderstaand assortimentsoverzicht geeft een indruk van de mogelijkheden van GNS Nederland. Gezien de enorme diversiteit aan afmetingen is enkel melding gemaakt van leverbare uitvoeringen en drukgroepen. De producten zijn leverbaar in DIN en ASME / ANSI kwaliteiten en desgewenst met certificaat volgens EN10204, aanvullende PMI tests e.d..

Bent u benieuwd naar de mogelijkheden? Schroom niet om ons te benaderen. We staan u graag te woord en willen graag met u meedenken over uw materiaalbehoeften. Onze mogelijkheden zullen u verrassen.

 Below mentioned program overview gives an impression of the possibilities of GNS. Given the enormous diversity in dimensions there is only mention made of available models and pressure classes. The products are available in DIN and ASME / ANSI qualities and optionally with certificates according to EN 10204, additional PMI tests etc.

Are you curious about the possibilities? Do not hesitate to contact us. We are always willing to help and would like to think along with you about your material needs. Our options will surprise you.

Stalen hogedruk fittingen

ASTM B16.11 / ASTM A105

Hochdruck Fittings aus Stahl / Carbon steel high pressure fittings

1: Vergelijkingstabel / Vergleichstabelle / comparison chart			Page
1.1	Buitenmaten inch / mm met schedule wanddikte afmetingen. Außenmaßen inch / mm mit Schedule Wandstärken Outside dimensions inch / mm with schedule wall thicknesses		2
2: Stalen gesmede fittingen / Geschmiedene Fittings aus Stahl / Steel forged fittings			Page
2.1	Screwed fittings 3000 / 6000 / 9000 lbs with NPT / BSP thread	ASTM B16.11	3
2.2	Socket weld fittings 3000 / 6000 / 9000 lbs with NPT / BSP thread	ASTM B16.11	4
2.3	Outlets (O'lets) 3000 / 6000 / 9000 lbs	ASTM B16.11	5



GNS NEDERLAND

FLEXIBLE METAL SERVICE & DISTRIBUTION

1 Overzichtstabel / Übersichtstabelle / Overview table

1.1 Aansluitmaten inch / mm met *schedule* wanddikte afmetingen.

Anschlußmaße inch / mm mit *schedule* Wandstärken.

Connection dimensions inch / mm with *schedule* wall thicknesses.

DN NW	NPS (inch)	EN / ISO (mm)	DIN Reihe 1	(mm) * Reihe 2	ANSI ASME (mm)	Schedule (mm)													
						5	10	20	30	40	60	80	100	120	160	XXS			
							10s			Std		XS							
6	1/8	10,2	10,2	-	10,29	0,89	1,24		1,45	1,73		2,41							
8	1/4	13,5	13,5	-	13,72	1,25	1,65		1,85	2,24		3,02							
10	3/8	17,2	17,2	14	17,14	1,24	1,65		1,85	2,31		3,20							
15	1/2	21,3	21,3	20	21,34	1,65	2,11		2,41	2,77		3,73			4,78	7,47			
20	3/4	26,9	26,9	25	26,67	1,65	2,11		2,41	2,87		3,91			5,56	7,82			
25	1	33,7	33,7	30	33,40	1,65	2,77		2,90	3,38		4,55			6,35	9,09			
32	1 ¼	42,4	42,4	38	42,16	1,65	2,77		2,97	3,56		4,85			6,35	9,70			
40	1 ½	48,3	48,3	44,5	48,26	1,65	2,77		3,18	3,68		5,08			7,14	10,16			
50	2	60,3	60,3	57	60,33	1,65	2,77		3,18	3,91		5,54			8,74	11,07			
65	2 ½	76,1	76,1	-	73,02	2,11	3,05		4,78	5,16		7,01			9,53	14,02			
80	3	88,9	88,9	-	88,90	2,11	3,05		4,78	5,49		7,62			11,13	15,24			
90	3 ½	101,6	-	-	101,60	2,11	3,05		4,78	5,74		8,08			13,49	16,15			

DN NW	NPS (inch)	EN / ISO (mm)	DIN Reihe 1	(mm) * Reihe 2	ANSI ASME (mm)	Schedule (mm)													
						5	10	20	30	40	60	80	100	120	140	160	XXS		
							10s			Std		XS							
100	4	114,3	114,3	108	114,30	2,11	3,05		4,78	6,02	7,14	8,56		11,10		13,49	17,12		
115	4 ½	-	-	-	127,00					6,27		9,02					18,03		
125	5	139,7	139,7	133	141,30	2,77	3,40			6,55		9,53		12,70		15,88	19,05		
150	6	168,3	168,3	159	168,28	2,77	3,40			7,11		10,97		14,27		18,26	21,95		
-	7	193,7	193,7	-	193,68					7,65		12,70					22,22		
200	8	219,1	219,1	216	219,08	2,77	3,76	6,35	7,04	8,18	10,31	12,70	15,09	18,26	20,62	23,01	22,22		
-	9	244,5	-	-	244,48					8,69		12,70							

DN NW	NPS (inch)	EN / ISO (mm)	DIN (mm) * Reihe 1	(mm) * Reihe 2	ANSI ASME (mm)	Schedule (mm)													
						5s	5	10	20	30	Std	40	60	XS	80	100	120	140	160
250	10	273	273	267	273,05	3,40	3,40	4,19	6,35	7,80	9,27	9,27	12,70	12,70	15,09	18,26	21,44	25,40	28,60
300	12	323,9	323,9	318	323,85	3,96	4,19	4,57	6,35	8,38	9,53	10,31	14,27	12,70	17,47	21,44	25,40	28,60	33,33
350	14	355,6	355,5	368	355,60	3,96	3,96	6,35	7,93	9,53	9,53	11,10	15,09	12,70	19,05	23,82	27,76	31,75	35,71
400	16	406,4	406,4	419	406,40	4,19	4,19	6,35	7,93	9,53	9,53	12,70	16,64	12,70	21,44	26,19	30,96	36,50	40,46
450	18	457,2	457,2	470	457,20	4,19	4,19	6,35	7,93	11,10	9,53	14,27	19,05	12,70	23,82	29,36	34,93	39,68	45,24
500	20	508	508	521	508,00	4,78	6,35	6,35	9,53	12,70	9,53	15,09	20,62	12,70	26,19	32,51	38,10	44,45	49,99
550	22	559	-	-	558,80	4,78	6,35	6,35	9,53	12,70	9,53	15,90	22,22	12,70	28,60	34,93	41,28	47,63	53,98
600	24	610	610	622	609,60	5,54	5,54	6,35	9,53	14,27	9,53	17,47	24,61	12,70	30,96	38,89	46,03	52,38	59,51

DN NW	NPS (inch)	EN / ISO (mm)	DIN (mm) * Reihe 1	(mm) * Reihe 2	ANSI ASME (mm)	Schedule (mm)													
						5s	10s	10	20	30	Std	40	XS						
650	26	660	-	-	660,40			7,93	12,70		9,53		12,70						
700	28	711	711	720	711,20			7,93	12,70	15,88	9,53		12,70						
750	30	762	-	-	762,00	6,35	7,93	7,93	12,70	15,88	9,53		12,70						
800	32	813	813	820	812,80			7,93	12,70	15,88	9,53	17,48	12,70						
850	34	864	-	-	863,60			7,93	12,70	15,88	9,53	17,48	12,70						
900	36	914	914	920	914,40			7,93		15,88	9,53	19,05	12,70						



Vermelde aansluitmaten volgens *Reihe 1* zijn gelijk aan EN / ISO. Vermelde aansluitmaten volgens *Reihe 2* zijn afwijkend van EN / ISO.

Angegebene anschlussmaße nach *Reihe 1* sind ähnlich EN / ISO. Angegebene anschlussmaße nach *Reihe 2* sind abweichend von EN / ISO.

Listed connection dimensions acc. *Reihe 1* are similar to EN / ISO. Listed connection dimensions acc. *Reihe 2* are different from EN / ISO.



2.1 Screwed fittings 3000 lbs / 6000 lbs / 9000 lbs with NPT / BSP thread

2.1.1



Elbow 90°

2.1.2



Elbow 45°

2.1.3



Street elbow

2.1.4



Cap

2.1.5



Cross

2.1.6



Tee

2.1.7



Reducing Tee

2.1.8



Coupling

2.1.9



Half coupling

2.1.10



Reducing coupling

2.1.11



Union F/F

2.1.12



Union M/F

2.1.13



Round head plug

2.1.14



Haexagon head plug

2.1.15



Square head plug

2.1.16



Hexagon nipple

2.1.17



Hexagon red nipple

2.1.18



Hexagon bushing

2.1.19



Reducing swage nipple

2.1.20



Pipe nipple

2.1.21



Half nipple



2.2 Socket weld fittings 3000 lbs / 6000 lbs / 9000 lbs

2.2.1



Elbow 90°

2.2.2



Elbow 45°

2.2.3



Cap

2.2.4



Cross

2.2.5



Equal T

2.2.6



Reducing T

2.2.7



Coupling

2.2.8



Half coupling

2.2.9



Reducing coupling

2.2.10



Reducing insert

2.2.11



Reducing swage nipple

2.2.12



Union

2.2.13



Boss



2.3 Outlets (O'lets) 3000 lbs / 6000 lbs / 9000 lbs *

2.3.1



Buttweld outlets

2.3.2



Socket outlets

2.3.3



Screwed outlets

* Please contact us for the requested type.